

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
25 August 2005 (25.08.2005)

PCT

(10) International Publication Number  
**WO 2005/077626 A1**

(51) International Patent Classification<sup>7</sup>: **B27K 3/08**  
(21) International Application Number:  
PCT/NZ2005/000022

(22) International Filing Date: 18 February 2005 (18.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
531217 18 February 2004 (18.02.2004) NZ

(71) Applicant (for all designated States except US): **NEW ZEALAND FOREST RESEARCH INSTITUTE LIMITED** [NZ/NZ]; Sala Street, ROTORUA (NZ).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **NASHERI, Kouroush** [NZ/NZ]; 4 Tupara Crescent, ROTORUA, 3201 (NZ). **DURBIN, Gavin James** [NZ/NZ]; 7A Mountain Road, ROTORUA, 3201 (NZ).


(74) Agents: **ADAMS, Matthew, D** et al.; A J Park, 6th Floor Huddart Parker Building, PO Box 949, Wellington, 6015 (NZ).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: IMPREGNATION PROCESS



(57) Abstract: The invention relates to a process for impregnating wood or wood based material. A working solution is preheated to a temperature above the atmospheric boiling point ("a super hot temperature") above the atmospheric boiling point ("a super hot temperature") of the working solution, at an elevated pressure sufficient to maintain the working solution in the liquid phase. The working solution is contacted with a wood or wood based material at a super hot temperature and an elevated pressure to cause impregnation of the solution into the wood or wood based material. The impregnated wood or wood based material and any remaining working solution, waste material and/or by-products are then separated.

WO 2005/077626 A1



**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*